

A1  
C12

at least one input device in communication with the processor; and  
a light source attached to a top side of the housing and in communication with the  
processor, wherein the motion detector communicates a signal to the processor upon detection of  
motion of the device, and wherein the processor effects the light source to be lit upon receipt of  
the signal.

---

Sub. B2

6. (Amended) A remote control device, comprising:  
a housing,  
a processor located in the housing;  
a motion detector in communication with the processor;  
at least one output device in communication with the processor;  
a light source located in the housing and in communication with the processor, wherein  
the motion detector communicates a signal to the processor upon detection of motion of the  
device, and wherein the processor effects the light source to be lit upon receipt of the signal; and  
a semi-transparent area located on a top side of the housing and having no input function,  
wherein the semi-transparent area is backlit when the light source is lit.

---

Sub. B3

8. (Amended) A remote control device, comprising:  
a housing;  
a processor located in the housing;  
a motion detector in communication with the processor;  
a keypad located on a top side of the housing and in communication with the processor,  
the keypad having a plurality of keys; and  
a plurality of lights attached to a top side of the housing and in communication with the  
processor, each of the lights corresponding to at least one of the keys, wherein the motion

A3  
cont.

23  
CML  
detector communicates a signal to the processor upon detection of motion of the device, and wherein the processor effects the plurality of lights to be lit upon receipt of the signal.

---

10. (Amended) A remote control device, comprising:  
a housing;  
a processor located in the housing;  
a motion detector in communication with the processor;  
at least one input device in communication with the processor; and  
a light source in communication with the processor, wherein the motion detector communicates a signal to the processor upon detection of motion of the device, wherein the processor effects the light source to be lit upon receipt of the signal, and wherein a portion of the input device is backlit upon lighting of the light source.

24  
Sub. B4  
11. (Amended) A remote control device, comprising:  
a housing;  
a processor located in the housing;  
a motion detector in communication with the processor;  
at least one input device in communication with the processor;  
a light source in communication with the processor, wherein the motion detector communicates a signal to the processor upon detection of motion of the device, wherein the processor effects the light source to be lit upon receipt of the signal, and wherein the input device is backlit upon lighting of the light source; and  
a user-controllable switch in communication with the light source for disabling the lighting of the light source.

---